

```
[local] Redback# show hardware ?
backplane  Display backplane hardware information
card       Display hardware information for a specific card
detail     Display detail hardware information for all cards
fantray    Display fantray hardware information
|          Output Modifiers
<cr>
```

```
[local]Redback#
[local]Redback# show hardware card 3 detail
```

```
Slot           : 3                Type           : ether-12-port
Serial No      : 7U055090601012   Hardware Rev   : 05
EEPROM id/ver  : 0x5a/4                Mfg Date      : 15-SEP-2006
```

SysFpga rev	: 0x7	SysFpga file rev	: N/A
LimFpga rev	: 0x5	LimFpga file rev	: 0x5
FlipFpga rev	: 0x9	FlipFpga file rev	: 0x9

← FPGA version - Important during upgrade

```
IPPA memory    : 256 MB           EPPA memory    : 256 MB
Voltage 1.5V   : 1.509 (+1%)      Voltage 1.8V   : 1.785 (-1%)
Voltage 2.6V   : 2.612 (-1%)      Voltage 3.3V   : 3.389 (-0%)
```

```
Temperature    : NORMAL (34 C)
Card Status    : HW initialized
ODD Status     : Not Available
```

```
POD Status     : Success
```

← Power-on diagnostics positive

Fail LED	: Off	Active LED	: On
Standby LED	: Invalid		

← LED status on card

```
Chass Entitlement : SE400/SE800
Ports Entitled   : All
Active Alarms    : NONE
```

```
[local]Redback#
```